

FD-HG8421A - XPON ONU Dual Band Specifications

Contents

1.Overview.....	3
1.1 Product Positioning.....	3
1.2 Network Mode.....	3
2.Hardware Features.....	4
2.1 Interface of device.....	4
2.2 Indicators of device.....	5
3.Technical specifications.....	5
3.1 Physical structure, Environment and Electrical parameter.....	5
3.2 GPON Interface Specifications.....	6
3.3 WIFI Specifications.....	6
3.4 POTS Specifications.....	7
3.5 Special function.....	7

1.OVERVIEW

1.1 Product Positioning

FD-HG8421A terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. The box is based on the mature Gigabit GPON technology, which have high ratio of performance to price, and the technology of 802.11 ac/n WiFi , Layer 2/3, and high quality VoIP as well. They are highly reliable and easy to maintain, with guaranteed QoS for different service. And It is fully compliant with technical regulations such as ITU-T G.984.x and technical requirement of GPON Equipment (V2.1 and above version) from China Telecom.

1.2 Network Mode

FD-HG8421A is the FTTH mode terminal equipment which designed for indoor applications. Specific application refers to Picture 1-1



Picture 1-1 FD-HG8421A products Network diagram

2.HARDWARE FEATURES

2.1 Interface of device

FD-HG8421A product figure as Picture 2-1



Picture 2-1 FD-HG8421A product figure

Table 2-1 Description FD-HG8421A equipment Interface

Port Type	Function
PON port	Connect PON port with internet by SC type, single mode optical fiber cable
FXS port	Connect the telephone with FXS port by telephone wire
LAN ~LAN4 port	RJ45Port connects to local internet, 1 GE port and 3 FE port automatically
Reset button (RST)	Press down reset button and keep 5 seconds to make the device restart and recover from the factory default Settings.
PWR port (DC12V)	Connect with power adapter
Power turn on/off	Power turn on/off

2.2 Indicators of device

Table 2-2 FD-HG8421A LED statement

Indicators	status	Description
POWER	Light on	ONU power supply normally
	Light off	ONU no power supply
PON	Light on	ONU link active
	Blink	ONU manage to link
	Light off	ONU receiving power rate lower than optical receiver sensitivity
LOS	Blink	Device does not receive optical signals.
	Light off	Device has received optical signal.
2.4G	Light on	WiFi turn on
	Light off	Device is power off or WiFi turn off
	Blink	WiFi turn on and with ongoing data transmission
5G	Light on	WiFi turn on
	Light off	Device is power off or WiFi turn off
	Blink	WiFi turn on and with ongoing data transmission
INTERNET	Light on	Internet is effective.
	Light off	Internet is ineffective.
LAN1~4	Light on	network port linked, but no data transmitting
	Blink	network port data pass
	Light off	ONU no power supply or internet cable unlink
FXS	Light on	Registered to the SIP server and can be used
	Light off	It is not registered to the SIP server

3. TECHNICAL SPECIFICATIONS

3.1 Physical structure, Environment and Electrical parameter

Table 3-1 FD-HG8421A specification and working environment

Parameter	Nominal
Dimension	226mm×148mm×30mm (L×W×H)
Net weight	0.3kg
Typical power consumption	<10W
Noise	None
Cooling style	Naturally cooling
Power supply	12V DC (By external AC/DC adapter)

Installation style	Support PC, wall mount or put inside of information box.
Environment	-5~50℃
Atmospheric pressure	70~106Kpa
MTBF	50,000hours
MTTR	30minutes
Parameter	Nominal

3.2 GPON Interface Specifications

Table 3-2 FD-HG8421A GPON Interface

Parameter	Nominal
Connector style	SC/PC
PON quantity	1
Fiber style	Single mode
Wavelength	TX: 1310 +/-20nm RX: 1490 +/-10nm
PON interface standard	ITU-T G.984.2/ITU-T G.984.3/ITU-TG.988 Class B+
PON interface receiving rate	2.488Gpbs
PON interface transmitting rate	1.244Gpbs
Output optical power	Min: 0.5dBm Max: +5dBm
Opticalreceiver sensitivity	Precede -29dBm
The length of the optical link	Max 20km

3.3 WIFI Specifications

Table 3-3 FD-HG8421A WIFI Specifications

Standard		IEEE 802.11 ac/b/g/n
WiFi parameter	Frequency	2.4~2.4835GHz 5GHz: Low frequency 5.15GHz~5.25GHz、 Middle frequency 5.25GHz~5.35GHz、 High frequency 5.725GHz~5.825GHz
	Transmission speed	2.4GHz Frequency: IEEE 802.11b : 11/5.5/2/1M(Auto) IEEE 802.11g: 54/48/36/24/18/12/9/6(Auto) IEEE 802.11n: 270/243/216/162/108/81/54/27Mbps, up to 300Mbps 5GHz Frequency: IEEE 802.11n: Highest transmission speed up to 300Mbps IEEE 802.11ac : Highest transmission speed up to 867Mbps

Channel number	2.4GHz : 13 5GHz: 4
Spread-spectrum Technique	DSSS(Direct sequence spread spectrum)
Data Modulation	DBPSK、DQPSK、CCK and OFDM(BPSK/QPSK/16-QAM/64-QAM)
Sensitivity@PER (Package error rate)	270M: -68dBm@10% PER; 130M: -68dBm@10% PER; 108M: -68dBm@10% PER; 54M: -68dBm@10% PER 11M: -85dBm@8% PER; 6M: -88dBm@10% PER 1M: -90dBm@8% PER;
Transmission distance	Indoor Maximum 120 meters; Outdoor Maximum 360 meters(The distance depends on the environment)
RF power	20dBm EIRP
Antenna	5dBi Antennas

3.4 POTS Specifications

- support SIP voice protocol
- support H.248 voice protocol
- SIP protocol: ISP provide the port number of the main SIP proxy server and terminal VOIP
- Value range is 1-65535, system default value is 5060
- H.248 protocol: ISP provide port number of the spare MGC server and VOIP terminal
- Value range is 1~65535, system default value is 2944
- Port ringing current voltage: 50±10VAC, 30±10H
- Port type POTS(VOIP)
- Support G.711 A-Law/u-Law,G729A/B,G.723.1-5.3/6.3,G.726.etc.voice coding/compressed technology

3.5 Special function

- Support TR069,NAT,DMZ,DNS features
- Support Multiple ssid
- Support Multiple VLAN
- Support IPV6 ,PPPoE, DHCP and Static IP configuration for WAN Interface
- Support IP, MAC filtering, Firewall Functionality in routed mode