

# **FD-HG8421C - XPON ONU Dual Band Specifications**

# Contents

<b>1.Overview.....</b>	<b>3</b>
1.1 Product Introduction.....	3
1.2 Network Mode.....	3
<b>2.Hardware Features.....</b>	<b>4</b>
2.1 Interface of device.....	4
2.2 Indicators of device.....	5
<b>3.Technical specifications.....</b>	<b>6</b>
3.1 Physical structure, Environment and Electrical parameter.....	6
3.2 GPON Interface Specifications.....	6
3.3 CATV optical receiver specifications.....	7
3.4 Wi-Fi Specifications.....	9
3.5 POTS Specifications.....	9
3.6 Special function.....	9

# 1.OVERVIEW


---

## 1.1 Product Introduction

FD-HG8421C terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. The box is based on the mature Gigabit GPON technology, which have high ratio of performance to price, and the technology of 802.11 ac/n Wi-Fi , Layer 2/3, and high quality VoIP as well. They are highly reliable and easy to maintain, with guaranteed QoS for different service. And It is fully compliant with technical regulations such as ITU-T G.984.x and technical requirement of GPON Equipment (V2.1 and above version) from China Telecom.

## 1.2 Network Mode

FD-HG8421C is the FTTH mode terminal equipment which designed for indoor applications. Specific application refers to Picture 1-1



Picture 1-1 FD-HG8421C products Network diagram



## 2.HARDWARE FEATURES

### 2.1 Interface of device

FD-HG8421C product figure as Picture 2-1



Picture 2-1 FD-HG8421A product figure

Table 2-1 Description FD-HG8421C equipment Interface

Port Type	Function
FXS port	Connect the telephone with FXS port by telephone wire
CATV port	Connect PON port with internet by SC/APC, Built-in WDM, it can transmit optical signals of 1550nm, 1310nm and 1490nm wavelengths.
RF port	Connect the set-top box via coaxial cable.
LAN 1~4 port	RJ45 Port connects to local internet,4 GE port
Reset button (RST)	Press down reset button and keep 5 seconds to make the device restart and

	recover from the factory default Settings.
WPS button (WPS)	WPS: Press for 3 seconds and press the WPS button of other Wi-Fi devices within 2 minutes to start standard WPS negotiation.
PWR port (DC12 V)	Connect with power adapter
Power turn on/off	Power turn on/off

## 2.2 Indicators of device

Indicators	status	Description
POWER	Light on	ONU power supply normally
	Light off	ONU no power supply
	Blink	Enable WPS function
PON	Light on	ONU link active
	Blink	ONU manage to link
	Light off	ONU receiving power rate lower than optical receiver sensitivity
LOS	Blink(Red)	Device does not receive optical signals.
	Light off	Device has received optical signal.
INTERNET	Light on	Internet is effective.
	Light off	internet is ineffective.
LAN1~4	Light on	network port linked, but no data transmitting
	Blink	network port data pass
	Light off	The ONU is not powered on or the network cable is disconnected
WIFI	Light on	Wi-Fi turn on
	Light off	Device is power off or Wi-Fi turn off
	Blink	Wi-Fi turn on and with ongoing data transmission
FXS	Light off	VOIP account is not used
	Every 1s blink	SIP server is not registered
	Light on	Registered to the SIP server and can be used
	Every 0.25s blink	Send and receive voice data
CATV	Light on	normal work
	Blink	CATV function is turned off

## 3. TECHNICAL SPECIFICATIONS

### 3.1 Physical structure, Environment and Electrical parameter

Table 3-1 FD-HG8421C specification and working environment

Parameter	Nominal
Dimension	176mm×112mm×31mm (L×W×H)
Net weight	0.35kg
Typical power consumption	<12W
Noise	None
Cooling style	Naturally cooling
Power supply	12V DC (By external AC/DC adapter)
Installation style	Support PC, wall mount or put inside of information box.
Environment	-5~50°C
Atmospheric pressure	70~106Kpa
MTBF	50,000hours@25°C
MTTR	30minutes

### 3.2 GPON Interface Specifications

Table 3-2 FD-HG8421C GPON Interface

Parameter	Nominal
Connector style	SC/APC
PON quantity	1
Fiber style	Single mode
Wavelength	TX: 1310 +/-20nm RX: 1490 +/-10nm
PON interface standard	ITU-T G.984.2/ITU-T G.984.3/ITU-TG.988 Class B+
PON interface receiving rate	2.488Gpbs
PON interface transmitting rate	1.244Gpbs
Output optical power	Min: 0.5dBm                      Max: +5dBm
Opticalreceiver sensitivity	Precede -28dBm
The length of the optical link	Max 20km

### 3.3 CATV optical receiver specifications

Table 3-3 CATV Optical receiver parameter

Item		Unit	Parameter
Optical parameter	Receiving optical wavelength	nm	1200~1650
	Receiving optical power	dBm	-18~+0
	Reflection loss	dB	≥50
	Connector	-	SC/APC
	Fiber type	-	Single mode
	Isolation (WDM)	Forward channel	dB
Reflection channel		dB	≥22
RF parameter	Frequency	MHz	47 ~ 1000
	In-band flatness	dB	±1
	Output reflection loss	dB	≥14
	Nominal output level	dBuV	=75±1 (AGC range: -15~ -2dBm)
	Attenuation range	dB	-18~0
	C/N	dB	≥ 46
	C/CTB	dB	≥ 65
	C/CSO	dB	≥ 65
Output impedance	Ω	75	
Others	Power supply (DC)	V	5
	Power consumption	W	≤1.5
	Working temperature	°C	0 ~ +45
	Storage temperature	°C	-40~ +75
	Relative humidity	%	Maximum 95% non-condensing

### 3.4 Wi-Fi Specifications

Table 3-3 FD-HG8421C Wi-Fi Specifications

Standard		IEEE 802.11 ac/b/g/n
WiFi parameter	Frequency	2.4~2.4835GHz 5GHz: Low frequency 5.15GHz~5.25GHz、 Middle frequency 5.25GHz~5.35GHz、 High frequency 5.725GHz~5.825GHz
	Transmission speed	2.4GHz Frequency: IEEE 802.11b : 11/5.5/2/1M(Auto) IEEE 802.11g: 54/48/36/24/18/12/9/6(Auto) IEEE 802.11n: 270/243/216/162/108/81/54/27Mbps,up to 300Mbps
		5GHz Frequency: IEEE 802.11n: Highest transmission speed up to 300Mbps IEEE 802.11ac : Highest transmission speed up to 867Mbps
	Channel number	2.4GHz : 13 5GHz: 4
	Spread-spectrum Technique	DSSS(Direct sequence spread spectrum)
	Data Modulation	DBPSK、DQPSK、CCK and OFDM(BPSK/QPSK/16-QAM/64-QAM)
	Sensitivity@PER (Package error rate)	270M: -68dBm@10% PER; 130M: -68dBm@10% PER; 108M: -68dBm@10% PER; 54M: -68dBm@10% PER 11M: -85dBm@8% PER; 6M: -88dBm@10% PER 1M: -90dBm@8% PER;
	Transmission distance	Indoor Maximum 120 meters; Outdoor Maximum 360 meters(The distance depends on the environment)
	RF power	20dBm EIRP
	Antenna	5dBi Antennas



### 3.5 POTS Specifications

- support SIP voice protocol
- support H.248 voice protocol
- SIP protocol: ISP provide the port number of the main SIP proxy server and terminal VO
- Value range is 1-65535, system default value is 5060
- H.248 protocol: ISP provide port number of the spare MGC server and VOIP terminal
- Value range is 1~65535, system default value is 2944
- Port ringing current voltage: 50±10VAC, 30±10H
- Port type POTS(VOIP)
- Support G.711 A-Law/u-Law,G729A/B,G.723.1-5.3/6.3,G.726.etc.voice coding/comp technology

### 3.6 Special function

- Support TR069,NAT,DMZ,DNS features
- Support Multiple ssid
- Support MU-MIMO
- Support Easy-Mesh(optional)
- Support Multiple VLAN
- Support IPV6 ,PPPoE, DHCP and Static IP configuration for WAN Interface
- Support IP, MAC filtering, Firewall Functionality in routed mode
- Support for XPON, adaptive EPON or GPON OLT on the network