

4 WAY HARDLINE OUTDOOR TAPS

Value X: 8,11, 14, 17, 20, 23, 26 dB

FEATURES

- 5 -1000 MHz
- High Isolation, Low Thru-loss
- Captive Hardware to Prevent Loss During Installation
- Interlocking Tongue/Groove Plate
- Superior Interwoven Gasket, -100dB RFI Shielding
- Stainless Steel Clamp, can be used for Aerial or Pedestal Mounting
- Fused Output Ports
- Brass F-Port with Neoprene Gasket Seals
- Power Passing
- 360° Aluminum Drip Wells



TECHNICAL SPECIFICATIONS								
ITEM / dB VALUE		8	11	14	17	20	23	26
INSERTION LOSS (IN – OUT) (dB)	5 - 65 MHz	-	≤ 3.3	≤ 3.3	≤ 1.5	≤ 1.0	≤ 0.8	≤ 0.8
	65 - 550MHz	-	≤ 4.1	≤ 4.1	≤ 1.7	≤ 0.8	≤ 0.7	≤ 0.7
	550 - 750 MHz	-	≤ 4.6	≤ 4.6	≤ 2.3	≤ 1.2	≤ 0.8	≤ 0.8
	750 - 1000MHz	-	≤ 5.0	≤ 5.0	≤ 3.5	≤ 2.5	≤ 2.0	≤ 2.0
TAP LOSS	5 - 1000MHz	±1.5	±1.8	±1.5	±1.5	±1.5	±1.5	±1.5
ISOLATION (OUT – TAP) (dB)	5 - 65 MHz	-	≤ 22.0	≤ 26.0	≤ 30.2	≤ 28.0	≤ 30.0	≤ 30.0
	65 - 550MHz	-	≤ 28.0	≤ 28.0	≤ 28.0	≤ 28.0	≤ 29.0	≤ 29.0
	550 - 750 MHz	-	≤ 27.0	≤ 27.0	≤ 26.0	≤ 27.0	≤ 29.0	≤ 29.0
	750 - 1000MHz	-	≤ 22.0	≤ 22.0	≤ 24.0	≤ 22.0	≤ 26.0	≤ 26.0
ISOLATION (TAP – TAP) dB	5 - 1000MHz	≥ 22.0	≤ 22.0	≤ 22.0	≤ 22.0	≤ 26.0	≤ 22.0	≤ 22.0
IN / OUT / TAP Return Loss (dB)	5 - 1000MHz	≥ 16.0	≤ 16.0	≤ 16.0	≤ 16.0	≤ 16.0	≤ 16.0	≤ 16.0
Frequency range					5 - 1000MHz			
Power Capability					12 Amp			
Hum Modulation					>65 dB (at 10 Amp)			
Impedance					75 ohm			
Connector					5/8" x 24 UNEF			